

ગરમ પાણીની ગેરંટી*



- ☀ કાટ રહિત સ્ટેન્ડ
- ☀ મજબુત સ્ટેન્ડ ડિઝાઇન
- ☀ ડિઝાઇનર ટેંક કેપ
- ☀ સરળતાથી બદલી શકાય તેવું ઇલેક્ટ્રીક બેક-અપ
- ☀ ખાસ વિકસાવેલ એન્ટી કોરોઝીવ કોંટિંગ



* શરતોને આધીન



* શરતોને આધીન

Solar Water Heater, Solar Panel, Solar Inverter, Heat Pump,
BLDC Solar Pump, E-bicycle



આપને મળતા ફાયદા :

- ☀ ગેસ અને વીજળીના વપરાશ વિના મેળવો આખું વર્ષ ગરમ પાણી
- ☀ કોઈપણ જાતનો મેન્ટેનન્સ ખર્ચ નહીં
- ☀ ગેસ અને ઇલેક્ટ્રીક ગીઝરની સરખામણીએ ૧૦૦% સુરક્ષિત

- ☀ ખાસ રીતે તૈયાર કરેલી ટ્રીપલ કોટેડ ગ્લાસ ટ્યુબ પાણી ઝડપથીગરમ કરવામાં મદદરૂપ
- ☀ ન્યુ આકર્ષક સ્ટેન્ડ
- ☀ શુન્ય સંચાલન ખર્ચ

Technical Specification :

Material	1.6mm Borosilicate 3.3 glass
Dimension	O.D. 47mm / 58mm / 70mm I.D. 37mm / 47mm / 54mm Length : 1500mm / 1800mm 2100mm
Glass Thickness	1.6mm
Absorptive Coating	CU - AL - N / SS (Three Layer)
Absorptance	>92% (Am1.5)
Amission	<8% (80°C)
Vacume	P < 5x10 ⁻³ PA
Stagnation temperature	>200° C
Heat loss	<0.8w / sq.mtr.
Maximum strength	0.8 MPa

Technical Specifications for Tank (Bharg Model)

Inner Tank	2.5mm Galvanized Iron (G.I) TIG & MIG Welded
Inner Coating	High Grade Emulsion GL Coating
Outer Cladding	0.45mm Galvanized Iron (G.I) with P P Powder Coating
Insulation	50mm PUF (38kg. / mt ³ density)
Stand	1.4 mm (G.I) with P P Powder Coating or 30 x 30 x 3mm M.S with P P Powder Coating
Connections	1"
Electric Backup Provision	1.25"

Technical Specifications for Tank (Ray Model)

Inner Tank	1.6mm Galvanized Iron (G.I) TIG or MIG Welded
Outer Cladding	0.45mm Galvanized Iron (G.I) with P P Powder Coating
Insulation	50mm PUF (38kg. / mt ³ density)
Stand	1.4 mm (G.I) with P P Powder Coating or 30 x 30 x 3mm M.S with P P Powder Coating
Connections	1"
Electric Backup Provision	1.25"

ઉપયોગીતા

- ☀ ઘર વપરાશ ગરમ પાણી માટે
- ☀ હોસ્ટેલ
- ☀ હોસ્પીટલ
- ☀ હોટેલ અને રેસ્ટોરન્ટ
- ☀ સ્વીમીંગ પુલ
- ☀ આરોગ્ય ક્લબ
- ☀ સ્ટીમ બોઈલરમાં ગરમ પાણી માટે



યુરાટોમ પ્રોજેક્ટ્સ



Uratom Solar (India) Pvt. Ltd.

Survey No.752 P1, National Highway 27, Near Chordi Village,
Gondal - 360 311. (Gujarat) India.

E-mail : care@uratom.com | Web : www.uratom.com

Customer Care :

Gujarat : +91 99250 99249

Authorised Dealers / Distributors:

